



99/12

PRODUCT BENEFITS

- Immediate access for light traffic (PSA)
- ColorReady® technology improves install accuracy
- High-strength, waterproof bond
- PSA performance with hard-set resilience
- LEED v4 contributing

RH 99%	pH 5-12	MVER 12 lbs	*DRY TIME 30-60 min	*WORKING TIME 12 hrs	CURE TIME 12 hrs	*LIGHT TRAFFIC 0 min	HEAVY TRAFFIC 24 hrs	ROLLING LOADS 48 hrs
-----------	------------	----------------	------------------------	-------------------------	---------------------	-------------------------	-------------------------	-------------------------

APPROVED FLOORING TYPES

- LVT/LVP
- Carpet tile (hard- and soft-backed)
- Sheet goods (vinyl, homogeneous, heterogeneous, fiberglass)
- Rubber (tile and sheet)
- WPC/WSC
- Cork-backed hard surface
- Cork underlayment
- VCT/VET
- Broadloom carpet (breathable and vinyl-backed)
- Carpet cushion to substrate
- Stair treads (rubber and vinyl)

APPLICATION METHODS

90-350 sf/gal

Note: Coverage range dependent upon substrate composition and porosity, application method and flooring type.

SUSTAINABILITY

- VOC content 11 g/L (meets SCAQMD Rule 1168)
- CDPH/EHLB Standard Method v1.2
- Does not contain methylene chloride and perchloroethylene
- Contributes to low emitting materials



Shelf Life: 2 Years

AVAILABLE IN 4-GALLON PAILS

*Data icons reference PSA usage only. See technical data sheet for details.