



CLEANING AND MAINTENANCE

ACTIVE SPORTS RUBBER FLOORING CLEANING & MAINTENANCE GUIDE

INCLUDING: POST INSTALLATION CLEANING • REGULAR FLOOR MAINTENANCE
RESTORATIVE MAINTENANCE

CLEANING AND MAINTENANCE

ACTIVE SPORTS RUBBER FLOORING

CLEANING & MAINTENANCE GUIDE

FLOOR CARE & MAINTENANCE GUIDELINES

POST INSTALLATION

ACTIVE SPORTS rubber tiles do not include a protective finish when shipped from the manufacturing facility. It is highly recommended that the newly installed rubber be protected using a tarpaulin or other cover until the can be cleaned and/or sealed.

INITIAL CLEANING:

Do not wash the floor for at least 5 days after installation. An initial cleaning needs to be done to remove any dirt and grit from the job site and to prepare the floor prior to applying a sealer or finish. Failure to clean properly will cause bonding issues as well as the entrapment of dirt in the r.

To avoid possible damage to the flooring, the following should never be used:

- Steel wool or abrasive brushes
- Abrasive or alkaline cleaners
- Solvents of any type

The should be cleaned with a neutral cleaner.

1. Thoroughly sweep or vacuum the to remove all loose dirt, dust and debris.
2. Apply a neutral cleaner to the with a mop (or automatic scrubber). Follow the manufacturer's instructions.
3. Use a wet vac or mop to remove cleaning solution.
4. Rinse with clean, cold water. Remove all water with wet vac or mop. Allow rubber to dry thoroughly.
5. Follow the manufacturer's instructions for proper application of the sealer (if applicable).

Visit the company web site www.ultimaterb.com for recommended cleaners and sealers.

REGULAR FLOOR MAINTENANCE

A regular maintenance program is extremely important and will increase the life of the and The frequency of cleaning will depend on the amount of tra on the r. For general cleaning, a neutral cleaner should be used. See the company web site for more information on recommended cleaner products.

1. Thoroughly sweep or vacuum the to remove all loose dirt, dust and debris.
2. Apply a neutral cleaner to the with a mop (or automatic scrubber). Follow the manufacturer's instructions.
3. Use a Wet Vac or mop to remove cleaning solution.
4. Rinse with clean, cold water. Remove all water with wet vac or mop. Allow rubber to dry thoroughly.

* * * IMPORTANT * * *

To prevent slip and fall accidents, ALWAYS use a "WET FLOOR" sign when wet rubber flooring has been cleaned and is open to traffic.

RESTORATIVE FLOOR MAINTENANCE

When noticeable accumulation of dirt and other contaminants become embedded in the rubber a quality stripper should be used to remove the existing contaminant. Areas typically needing to be restored include high-traffic walkways, tight or confined spaces, and along baseboards.

After the stripper has been applied and removed per the manufacturer's instructions, a neutral cleaner should be applied to the stripped area. See general cleaning instructions on this page.

Once the the rubber flooring has been cleaned and allowed to dry, a sealer can be used to restore the appearance of the treated area.

Visit the Ultimate RB web site for recommended strippers, cleaners and sealer products.

CONTACT ALL SOUTH FLOORING

Contact All South Flooring Customer Service at 704-690-1871 with any questions pertaining to care or maintenance.