

Active Premium Specifications



Active Premium Specifications

Test Type	astm	color	black
Shore Hardness	d-2240	60 +/- 5	60 +/- 5
Density	d-792	65 lbs./cu.ft.	60 lbs./cu.ft.
Elongation (at break)	d-412	100%	85-125%
Tensile Strength	d-412	250 psi	250 psi
Taber Abrasion	d-3884	0.47	0.45
Flame Spread	e-84	135	135
Smoke Density	e-84	< 450	< 450
Compression Set	d-395	8.4%	< 12%
Voc Emissions	d-5116	0.5 mg/m ² or less	0.5 mg/m ² or less
Resistance To Chemicals	f-925-02	No Change	No Change
Static Load Limit	f-970	-0.001 in	-0.001 in
Electrostatic Propensity	aatcc 134-1996	neg 0.4 kv	-----
Die- C Tear	d-624	70 lb/in	95 ppi
Coefficient of Friction	d-1894-95	-----	wet 1.2 dry 1.2

Physical properties can vary by product type. Information above applies to this product only.



Interlocking Tile Dimensions

Tile Sizes

Interlocking

18" x 18" (0.4572m²) +/- 0.078"
 24" x 24" (0.61m²) +/- 0.078"
 36" x 36" (0.91m²) +/- 0.078"
 48" x 48" (1.2192m²) +/- 0.078"

Square

18" x 18" (0.4572m²) +/- 0.078"
 24" x 24" (0.61m²) +/- 0.078"
 36" x 36" (0.91m²) +/- 0.078"
 48" x 48" (1.2192m²) +/- 0.078"

*Thickness

Standard:

.134 in (3.4mm) to .472 in (12mm)

Tolerance

+/- 0.020"

Colored EPDM Granulate

0.0394 in (1mm) to .1181 in (3mm)

Black SBR Granulate

0.5 in (12.7mm)

Binder

Urethane

*Custom available.



Roll Dimensions

*Width

Standard:

4 ft. (1.22m)

*Length

Standard:

25 ft. (7.62m) & 50 ft. (15.24m)

Width Tolerances

48" Cut @ 48.5" +/- 0.24"

Colored EPDM Granulate

0.0394 in (1mm) to .1181 in (3mm)

*Thickness

Standard:

.134 in (3.4mm) to .472 in (12mm)

Black SBR Granulate

0.5 in (12.7mm)

Binder

Urethane

Tolerance

+/- 0.020"

The color concentration of the standard rolls and tiles is 20%.

*Custom available * 3 ft. (.91m) available as custom width