

LG HAUSYS FLOORS 2.2MM/20MIL HETEROGENEOUS SHEET		
COLLECTION NAME	Natural selection	
INVENTORY STYLE #		
STYLE NAME(S)		
SELLING STYLE #(S)	Natural selection	
TOTAL # SKU'S(COLORS)	8	
PRODUCT SPECIFICATIONS / CONTENT / CERTIFICATIONS	DETAILS	ADDITIONAL INFORMATION
Thickness	0.086in. , 2.2mm	
Wear Layer	20mil(0.02 in) , 0.5mm	
Glass Fiber	Yes	
Finishing / Coating	Waxable	
Nominal Dimensions (inches)	78 in wide , 68 ft ong	
Actual Dimensions (inches & mm)	Width : 78.75in , 2m / length : 68.58ft , 20.90 m	
Micro-Beveled	No	
Class / ASTM F1303	Type I, Grade I	
Backing Class	4-ply fused backing system, Class B	
Gloss Level	6~10	
Commercial Traffic	Heavy Commercial	
Added Antimicrobial	Yes	
Recycled Contents	100% Virgin Vinyl	
Backstamp info	None	
CE Certification	Yes	
PACKING SPEC'S	DETAILS	ADDITIONAL INFORMATION
Pallet Dimensions (L x W x H) / H: 2100mm	① 1200*910mm ② 910*910mm	
CARTONS / PALLET / CONTAINER	① 1200*910mm : 12Rolls/Pallet ② 910*910mm : 9Rolls/Pallet	
PALLETS PER CONTAINER	10 Pallets	20 foot container
SQYD PER ROLL	50SQYD	
SQYD PER PALLET	① 1200*910mm : 600SQYD ② 910*910mm : 450SQYD	
WEIGHT PER ROLL	337.7LBS/Roll	
WEIGHT PER PALLET (PALLET WEIGHT)	① 1200*910mm : 4,052.9LBS/Pallet ② 910*910mm : 3,039.7LBS/Pallet	
ROLL WRAPPING PAPER TYPE	Craft paper with pefoam Wrapping(PP Coating)	
PRODUCT PERFORMANCE / TESTING	PERFORMANCE	ASTM REQUIREMENT
ASTM D2047 Slip Resistance	>0.65 (wet, dry)	static coefficient of friction > 0.6 (ADA) * > 0.5OSHA
ASTM F970 Static Load	>1500psi	Max 0.005"
ASTM F1914 Residual Indentation	passes < 8%	Average less than 8%, maximum single reading 10%
ASTM F137 Flexibility	passes	No crack or brack
ASTM F925 Chemical Resistance	passes	more than slight change
ASTM F1514 Resistance to Heat	passes	E < 8
ASTM F1515 Resistance to Light	passes	E < 8
ASTM E648 Critical Radiant Flux	passes	>0.45watts/cm ² , NFPA Class I , Class II ³ 2.2 kW /m ²
ASTM E662 Optical Smoke Density	passes < 450	<450 in flaming and non flaming mode
TECHNICAL INFORMATION / DOCUMENTS		
Product Warranty	10 years for Commercial	
Installation Method	Full spread	
Approved Installation Methods	Glue down	
Recommended Adhesive(s)	Any approved Commerical Sheet adhesive	
Polished Required (Y/N)	None	