

LIFEWOOD-TRAIL

PRODUCT SPECIFICATIONS



Physical Construction	
Construction	LifeProtect Wood Fiber Based Flooring w/ SpillResist Technology
Size	8.03" Wide x 47.64" Long
Overall Thickness	10mm (8mm plank + 2mm attached pad)
Pieces Per Carton	7 Planks
Coverage Per Carton	1.728m ² / 18.60 sq. ft.
Weight Per Carton	12.56kg / 27.69 lbs
AC Wear Rating	AC4

Testing	
Sound Transmission Class (ASTM E90, E413)	152mm slab, drop ceiling, STC60
Impact Insulation Class IIC (ASTM E429, E989)	152mm slab, drop ceiling, IIC63
Large Ball Impact Resistance (NALFA LF-01)	≥1000mm
Small Ball Impact Resistance (NALFA LF-01)	≥200mm
Cleanability / Stain Resistance (NALFA LF-01)	Score < 20 - No More Than Slight Effect
Light Resistance (NALFA LF-01)	No More Than Slight Effect
Wear Resistance (NALFA LF-01)	AC4; ≥ 4,000 cycles
Thickness Swell (NALFA LF-01)	≤16%

Environmental

California CARB 93120 Phase 2 Compliant

TSCA Title VI Compliant

GreenGuard Gold Certified

Warranty

Limited Lifetime Residential

5-Year Light Commercial

Installation Method

Angle / Tap

